

EL465779674

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Priority Application Serial No. .... 09/161,512  
Priority Filing Date ..... September 28, 1998  
Inventor ..... James E. O'Toole et al.  
Assignee ..... Micron Technology, Inc.  
Priority Group Art Unit ..... 2635  
Priority Examiner ..... E. Holloway III  
Attorney's Docket No. .... MI40-325  
Title: Radio Frequency Data Communications Device

**PRELIMINARY AMENDMENT**

To: Assistant Commissioner for Patents  
Washington, D.C. 20231

From: Frederick M. Fliegel, Ph.D.  
Tel. 509-624-4276; Fax 509-838-3424  
Wells, St. John, Roberts, Gregory & Matkin P.S.  
601 W. First Avenue, Suite 1300  
Spokane, WA 99201-3828  
509-624-4276

**AMENDMENTS**

This is a preliminary amendment accompanying a Request for Continuation Application for the above-titled patent application. Prior to examining the application, please make the following amendments.

**In the Specification**

(i) On page 1, replace the paragraph beginning at line 4 and ending at line 6 with the paragraph shown below in clean form. Another version of this paragraph, marked to show the changes made, is attached in a separate page from this amendment, in accordance the provisions of 37 CFR §1.121(b)(1)(i)-(iii).

This application is a continuation of U.S. Patent Application Serial No. 09/161,512, filed on September 28, 1998, which is a divisional of U.S. Application Serial No. 08/705,043, filed on August 29, 1996, now U.S. Patent No. 6,130,602 (incorporated herein by reference), which claims priority from U.S. Provisional Application 60/017,900, filed May 13, 1996, titled "Radio Frequency Data Communication Device.

(ii) Replace the paragraph beginning at page 58, line 17 and ending at page 59, line 7 with the paragraph shown below in clean form. Another version of this paragraph, marked to show the changes made, is attached in a separate page from this amendment.

Another aspect of the invention provides a method for conserving power in a radio frequency identification device, the method comprising periodically switching from a sleep mode to a receiver on mode and performing the following tests to determine whether to further switch to a microprocessor on mode because a valid radio frequency signal is present: (a) determining if any radio frequency signal is present and, if so, proceeding to step (b); and, if not, returning to the sleep mode; (b) determining if the radio frequency signal is modulated and has a predetermined number of transitions per a predetermined period of time and, if so, proceeding to step (c); and, if not, returning to the sleep mode; and (c) determining if the modulated radio frequency signal has a predetermined number of transitions per a predetermined period of time different from the predetermined time of step (b)

and, if so, switching to the microprocessor on mode; and, if not, returning to the sleep mode.

(iii) Replace the paragraph beginning at page 86, line 13 and ending at page 87, line 9 with the paragraph shown below in clean form. Another version of this paragraph, marked to show the changes made, is attached in a separate page from this amendment.

If the power source 18 is a battery, the battery can take any suitable form. Preferably, the battery type will be selected depending on weight, size, and life requirements for a particular application. In one embodiment, the battery 18 is a thin profile button-type cell forming a small, thin energy cell more commonly utilized in watches and small electronic devices requiring a thin profile. A conventional button-type cell has a pair of electrodes, an anode formed by one face and a cathode formed by an opposite face. Exemplary button-type cells are disclosed in several pending U.S. patent applications including U.S. Patent Application Serial No. 08/205,957, "Button-Type Battery Having Bendable Construction and Angled Button-Type Battery," listing Mark E. Tuttle and Peter M. Blonsky as inventors, now U.S. Patent No. 5,432,027; U.S. Patent Application Serial No. 08/321,251, "Button-Type Batteries and Method of Forming Button-Type Batteries," listing Mark E. Tuttle as inventor, now U.S. Patent No. 5,494,495; and U.S. Patent Application Serial No. 08/348,543, "Method of Forming Button-Type Batteries and a Button-Type Battery Insulating and Sealing Gasket," listing Mark E. Tuttle as inventor, now U.S. Patent No. 5,662,718. These patent applications

and resulting patents are hereby incorporated by reference. In an alternative embodiment, the battery 18 comprises a series connected pair of button type cells. Instead of using a battery, any suitable power source can be employed.

(iv) Replace the paragraph beginning at page 89, line 1 and ending at page 89, line 18 with the paragraph shown below in clean form. Another version of this paragraph, marked to show the changes made, is attached in a separate page from this amendment.

Various U.S. patent applications, which are incorporated herein by reference, disclose features that are employed in various alternative embodiments of the invention: 08/092,147, filed July 15, 1993, "Wake Up Device for a Communications System", now abandoned, and continuation application 08/424,827, filed April 19, 1995, "Wake Up Device for a Communications System", now U.S. Patent No. 5,790,946; 08/281,384, filed July 27, 1994, "Communication System Having Transmitter Frequency Control", now U.S. Patent No. 5,568,512; 07/990,918, filed December 15, 1992, now U.S. Patent No. 5,365,551, "Data Communication Transceiver Using Identification Protocol"; 07/899,777, filed June 17, 1992, "Radio Frequency Identification Device (RFID) and Method of Manufacture, Including an Electrical Operating System and Method," now abandoned; 07/921,037, filed July 24, 1992, "Anti-Theft Method for Detecting The Unauthorized Opening of Containers and Baggage," now abandoned; 07/928,899, filed August 12, 1992, "Electrically Powered Postage Stamp or Mailing or Shipping Label Operative with Radio Frequency (RF) Communications," now

abandoned; and 08/032,384, filed on March 17, 1993, "Modulated Spread Spectrum in RF Identification Systems Method," now U.S. Patent No. 5,539,775.

(v) Replace the paragraph beginning at page 137, line 17 and ending at page 137, line 24 with the paragraph shown below in clean form. Another version of this paragraph, marked to show the changes made, is attached in a separate page from this amendment.

Preferably, the above technique for mounting integrated circuit 16 to card 20 (of Fig. 4) consists of a flip-chip mounting technique. One example of a flip-chip mounting technique is disclosed in pending U.S. Patent Application Serial No. 08/166,747, "Process of Manufacturing an Electrical Bonding Interconnect Having a Metal Bond Pad Portion and Having a Conductive Epoxy Portion Comprising an Oxide Reducing Agent," listing Rick Lake and Mark E. Tuttle as inventors, now U.S. Patent No. 5,480,834 and incorporated herein by reference.

(vi) Replace the paragraph beginning at page 209, line 13 and ending at page 209, line 18 with the paragraph shown below in clean form. Another version of this paragraph, marked to show the changes made, is attached in a separate page from this amendment.

The multiplier cell originally developed by Gilbert employed bipolar junction transistors. It is also known to employ MOS transistors to produce

a Gilbert multiplier cell. See, for example, Analog Integrated Circuits for Communication, Principles, Simulation and Design, Donald O. Pederson and Kartikeya Mayaram, Kluwer Academic Publishers, Third Printing, 1994, pp. 431-433.

### **In the Claims**

Cancel claims 1-252 and add new claims 253-284 as follows.

253. CMOS transmitter carrier circuitry configured to receive a digital clock signal, the circuitry comprising:

a phase locked loop including a voltage controlled oscillator configured to multiply the frequency of the digital clock signal by a predetermined multiple and control circuitry to maintain a desired frequency, the phase locked loop having an output providing a transmitter carrier; and

divider circuitry having an input coupled to the voltage controlled oscillator and receiving the multiplied frequency, the divider circuitry being configured to divide by the predetermined multiple, and the divider circuitry having an output coupled to the control circuitry.

254. CMOS transmitter carrier circuitry in accordance with claim 253, wherein:

the phase locked loop includes a loop filter coupled to the voltage controlled oscillator, and the control circuitry comprises:

a phase-frequency detector coupled to the divider circuitry output ; and  
a charge pump, the phase-frequency detector and the charge pump being coupled to the voltage controlled oscillator and to the loop filter, wherein the loop filter is a passive loop filter.

255. CMOS transmitter carrier circuitry in accordance with claim 253, wherein the voltage controlled oscillator has a plurality of outputs that are configured to be angularly spaced apart with respect to phase.

256. CMOS transmitter carrier circuitry in accordance with claim 255, further comprising a frequency doubler that receives at least some of the angularly spaced apart outputs of the voltage controlled oscillator, and that is configured to produce a signal with a frequency that is double the frequency of the outputs of the voltage controlled oscillator.

257. CMOS transmitter carrier circuitry in accordance with claim 256, wherein the frequency doubler comprises first and second Gilbert cells coupled together, a frequency generator configured to apply a first sinusoidal wave to the first Gilbert cell, and a phase shifter coupled between the first and second Gilbert cells to apply to the second Gilbert cell a sinusoidal wave that is shifted from the first sinusoidal wave.

258. CMOS transmitter carrier circuitry in accordance with claim 253, wherein the charge pump comprises:

a first charge pump coupled to a start-up circuit and configured to pump a frequency of the voltage controlled oscillator up in coarse, medium or medium fine steps in response to a start-up command from the start-up circuit; and

a second charge pump coupled to the control circuitry and configured to pump up or down the frequency of the voltage controlled oscillator in fine steps in response to signals from the control circuitry.

259. CMOS transmitter carrier circuitry in accordance with claim 258, wherein the start-up circuit is configured to initially invoke coarse or medium steps to pump up the frequency of the voltage controlled oscillator and is configured to invoke medium fine or fine steps when the start-up circuit determines that the frequency of the voltage controlled oscillator is within a few percent of a desired frequency.



260. A CMOS transmitter configured to receive a digital clock signal, the transmitter comprising:

a phase locked loop including a voltage controlled oscillator multiplying the frequency of the digital clock signal by a predetermined multiple, control circuitry coupled to the phase locked loop to maintain a desired frequency, the voltage controlled oscillator having a plurality of outputs that are angularly spaced apart with respect to phase, the phase locked loop having an output providing a transmitter carrier;

divider circuitry having an input coupled to at least one of the outputs of the voltage controlled oscillator, the divider circuitry being configured to divide by the predetermined multiple and having an output coupled to the control circuitry; and

a modulator coupled to the phase locked loop to use the transmitter carrier.

261. A CMOS transmitter in accordance with claim 260, wherein the voltage controlled oscillator has outputs that are spaced apart, with respect to phase in 45 degree intervals.

262. A CMOS transmitter in accordance with claim 261, wherein the predetermined multiple is sixteen.

263. A CMOS transmitter in accordance with claim 260, wherein the control circuitry comprises:

- a passive loop filter;
- a phase-frequency detector, the divider circuitry output being coupled to the phase-frequency detector; and
- a charge pump coupled to the voltage controlled oscillator and to the loop filter.

264. A CMOS transmitter in accordance with claim 263, wherein the charge pump comprises:

- a first charge pump coupled to a start-up circuit and configured to pump a frequency of the voltage controlled oscillator up in coarse, medium or medium fine steps in response to a start-up command from the start-up circuit; and
- a second charge pump coupled to the control circuitry and configured to pump up or down the frequency of the voltage controlled oscillator in fine steps in response to signals from the phase-frequency detector.

265. A CMOS transmitter in accordance with claim 264, wherein the start-up circuit is configured to initially invoke coarse or medium steps to pump up the frequency of the voltage controlled oscillator and is configured to invoke medium fine or fine steps when the start-up circuit determines that the frequency of the voltage controlled oscillator is within a few percent of a desired frequency.

266. An integrated circuit including carrier circuitry configured to provide a carrier for wireless communications, the carrier circuitry being configured to receive a digital clock signal, the carrier circuitry being defined by CMOS circuit elements, the carrier circuitry comprising:

a phase locked loop including a voltage controlled oscillator multiplying the frequency of the digital clock signal by a predetermined multiple, control circuitry configured compare the frequency and phase of the digital clock signal to a second signal and to issue pump up or pump down signals in response to the comparison, and a charge pump coupled to the control circuitry and configured to maintain a desired frequency in response to the pump up and pump down signals, the charge pump being configured to receive the pump up and pump down signals and produce an output having a voltage that varies in response to the pump up and pump down signals, the voltage controlled oscillator having an output, the phase locked loop having an output providing a transmitter carrier; and

divider circuitry having an input coupled to the output of the voltage controlled oscillator, the divider circuitry being configured to divide by the predetermined multiple and having an output coupled to the control circuitry.

267. An integrated circuit in accordance with claim 266, wherein the divider circuitry output defines the second signal and the control circuitry comprises a loop filter, a phase-frequency detector receiving the digital clock signal and the second signal and performing the comparison, the frequency of the output of the voltage controlled oscillator being configured to vary depending on a voltage provided by the loop filter to the voltage controlled oscillator.

268. An integrated circuit in accordance with claim 267 wherein the loop filter is configured to filter the output of the charge pump.

269. An integrated circuit in accordance with claim 266 wherein the predetermined multiple is sixteen.

270. An integrated circuit in accordance with claim 266, wherein the charge pump comprises:

a first charge pump coupled to a start-up circuit and configured to pump a frequency of the voltage controlled oscillator up in coarse, medium or medium fine steps in response to a start-up command from the start-up circuit; and

a second charge pump coupled to the control circuitry and configured to pump up or down the frequency of the voltage controlled oscillator in fine steps in response to signals from the phase-frequency detector.

271. An integrated circuit in accordance with claim 270, wherein the start-up circuit is configured to initially invoke coarse or medium steps to pump up the frequency of the voltage controlled oscillator and is configured to invoke medium fine or fine steps when the start-up circuit determines that the frequency of the voltage controlled oscillator is within a few percent of a desired frequency.

272. An integrated circuit including carrier circuitry configured to provide a carrier signal for wireless communications, the carrier circuitry being configured to receive a digital clock signal, the carrier circuitry being defined by CMOS circuit elements and comprising:

a phase locked loop including a voltage controlled oscillator configured to multiply the frequency of the digital clock signal by a predetermined multiple, control circuitry configured to receive the digital clock signal and compare the frequency and phase of the digital clock signal with a second signal and configured to issue pump up or pump down signals in response to the comparison, and a charge pump coupled to the control circuitry and to the voltage controlled oscillator to maintain a desired frequency in response to the pump up and pump down signals, the voltage controlled oscillator having a plurality of outputs that are angularly spaced apart with respect to phase, the phase locked loop having an output providing a transmitter carrier; and

divider circuitry having an input coupled to at least one of the outputs of the voltage controlled oscillator, the divider circuitry dividing by the predetermined multiple and having an output defining the second signal coupled to the control circuitry.

273. An integrated circuit in accordance with claim 272 wherein the predetermined multiple is sixteen.

274. An integrated circuit in accordance with claim 272 wherein the control circuitry comprises:

a passive loop filter coupled to the phase locked loop; and

a phase-frequency detector coupled to the charge pump;

and further comprising a first frequency doubler configured to receive at least some of the angularly spaced apart outputs of the voltage controlled oscillator, and that is configured to produce a signal with a frequency that is double the frequency of the outputs of the voltage controlled oscillator.

275. An integrated circuit in accordance with claim 274 and further comprising a second frequency doubler coupled to the first frequency doubler and that is configured to produce a signal with a frequency that is double the frequency of the signal produced by the first frequency doubler.

276. An integrated circuit in accordance with claim 272 and further comprising a first frequency doubler stage including a first frequency doubler configured to receive at least some of the angularly spaced apart outputs of the voltage controlled oscillator, and that is configured to produce a signal with a frequency that is double the frequency of the outputs of the voltage controlled oscillator, and a second frequency doubler that receives other of the angularly spaced apart outputs of the voltage controlled oscillator, and that is configured to produce a signal with a frequency that is double the frequency of the outputs of the voltage controlled oscillator.

277. An integrated circuit in accordance with claim 276 and further comprising a second frequency doubler stage coupled to the first frequency doubler stage and that is configured to produce a signal with a frequency that is double the frequency of the signals produced by the first frequency doubler stage.

278. An integrated circuit in accordance with claim 272, wherein the charge pump comprises:

a first charge pump coupled to a start-up circuit and configured to pump a frequency of the voltage controlled oscillator up in coarse, medium or medium fine steps in response to a start-up command from the start-up circuit; and

a second charge pump coupled to the control circuitry and configured to pump up or down the frequency of the voltage controlled oscillator in fine steps in response to signals from the phase-frequency detector.

	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2433	2434	2435	2436	2437	2438	2439	2440	2441	2442	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---



280. A communications system including a transmitter integrated circuit for wireless communications, the transmitter integrated circuit being configured to receive a digital clock signal, the transmitter integrated circuit being defined by CMOS circuit elements and comprising:

a phase locked loop including a voltage controlled oscillator configured to multiply the frequency of the digital clock signal by a predetermined multiple, control circuitry configured to receive the digital clock signal and to compare the frequency and phase of the digital clock signal with a second signal and to issue pump up or pump down signals in response to the comparison, and a charge pump coupled to the control circuitry and the voltage controlled oscillator to maintain a desired frequency in response to the pump up and pump down signals, the voltage controlled oscillator having a plurality of outputs that are angularly spaced apart with respect to phase, the phase locked loop having an output providing a transmitter carrier;

divider circuitry having an input coupled to at least at least one of the outputs of the voltage controlled oscillator, the divider circuitry dividing by the predetermined multiple and having an output defining the second signal coupled to the control circuitry; and

a modulator coupled to the voltage controlled oscillator.

281. A communications system in accordance with claim 280, wherein the voltage controlled oscillator includes a plurality of stages, one of the stages including a first transistor having a control electrode defining a first input, and first and second power electrodes, wherein the first power electrode defines a first node, wherein the stage further includes a second transistor having a control electrode defining a second input, and having first and second power electrodes, wherein the first power electrode of the second transistor defines a second node, wherein the stage further includes a current source connected to the second power electrodes of the first and second transistors, the current source being configured to direct current away from the second power electrodes of the first and second transistors, and wherein the stage further includes a variable resistance configured to couple the first and second nodes to a supply voltage.

282. A communications system in accordance with claim 280, wherein the control circuitry comprises:

- a passive loop filter coupled to the phase locked loop and to the charge pump; and

- a phase-frequency detector coupled to the second signal and to the charge pump.

283. A communications system in accordance with claim 280, wherein the charge pump comprises:

a first charge pump coupled to a start-up circuit and configured to pump a frequency of the voltage controlled oscillator up in coarse, medium or medium fine steps in response to a start-up command from the start-up circuit; and

a second charge pump coupled to the control circuitry and configured to pump up or down the frequency of the voltage controlled oscillator in fine steps in response to signals from the phase-frequency detector.

284. A communications system in accordance with claim 283, wherein the start-up circuit is configured to initially invoke coarse or medium steps to pump up the frequency of the voltage controlled oscillator and is configured to invoke medium fine or fine steps when the start-up circuit determines that the frequency of the voltage controlled oscillator is within a few percent of a desired frequency.

## **REMARKS**

Claims 1-252 have been canceled and new claims 253-284 have been added.

The amendments to the specification update the status of related applications and corrects minor informalities noted during review. No new matter is added by the amendments to the specification.

Another version of these paragraphs, marked to show the changes made and employing underlining to show additions and brackets to identify deletions, and including numbered paragraphs (i)-(vi) to illustrate correspondence with the clean versions of these paragraphs, is attached on separate pages from this amendment, in accordance the provisions of 37 CFR §1.121(b)(1)(i)-(iii).

New claims 253-284 are supported by text appearing at p. 83, line 5 through p. 279, line 3 of the specification as originally filed.

New claims 253-284 are also supported by p. 193, line 9 et seq. and associated Figs. of the specification as originally filed.

New claims 253-284 are also supported by p. 175, line 8 through p. 217, line 24, and in Figs. 8.0504, 8.050401, 8.050401AA-CK, 8.050402, 8.050402AA-CJ, 8.050403, 8.050403AA-BI, 8.050405 and 8.050405AA-EJ of the specification as originally filed.


No new matter is added by new claims 253-284. New claims 253-284 distinguish over the art of record and are allowable.

This application is believed to be in condition for allowance and action to that end is requested. The Examiner is requested to telephone the undersigned in the event that the next office action is one other than a Notice

of Allowance. The undersigned is available during normal business hours (Pacific Time Zone).

Attached hereto is a marked-up version of the changes made to the specification and claims by the current amendment. The attached page(s) are captioned "**Version with markings to show changes made.**"

Respectfully submitted,

Dated: March 30, 2009 By:   
Frederick M. Fliegel, Ph.D.  
Reg. No. 36,138

20090330 14:36:00

**VERSION WITH MARKINGS TO SHOW CHANGES MADE**

**AMENDMENTS**

(i) This application is a continuation of U.S. Patent Application Serial No. 09/161,512, filed on September 28, 1998, which is a divisional of U.S. Application Serial No. 08/705,043, filed on August 29, 1996, now U.S. Patent No. 6,130,602 (incorporated herein by reference), which claims priority from U.S. Provisional Application 60/017,900, filed May 13, 1996, titled "Radio Frequency Data Communication Device."

(ii) Another aspect of the invention provides a method for conserving power in a radio frequency identification device, the method comprising periodically switching from a sleep mode to a receiver on mode and performing the following tests to determine whether to further switch to a microprocessor on mode because a valid radio frequency signal is present: (a) determining if any radio frequency signal is present and, if so, proceeding to step (b); and, if not, returning to the sleep mode; (b) determining if the radio frequency signal is modulated and has a predetermined number of transitions per a predetermined period of time and, if so, proceeding to step (c); and, if not, returning to the sleep mode; and [©] (c) determining if the modulated radio frequency signal has a predetermined number of transitions per a predetermined period of time different from the predetermined time of step (b) and, if so, switching to the microprocessor on mode; and, if not, returning to the sleep mode.

(iii) If the power source 18 is a battery, the battery can take any suitable form. Preferably, the battery type will be selected depending on weight, size, and life requirements for a particular application. In one embodiment, the battery 18 is a thin profile button-type cell forming a small, thin energy cell more commonly utilized in watches and small electronic devices requiring a thin profile. A conventional button-type cell has a pair of electrodes, an anode formed by one face and a cathode formed by an opposite face. Exemplary button-type cells are disclosed in several pending U.S. patent applications including U.S. Patent Application Serial No. 08/205,957, "Button-Type Battery Having Bendable Construction and Angled Button-Type Battery," listing Mark E. Tuttle and Peter M. Blonsky as inventors, now U.S. Patent No. 5,432,027; U.S. Patent Application Serial No. 08/321,251, "Button-Type Batteries and Method of Forming Button-Type Batteries," listing Mark E. Tuttle as inventor, now U.S. Patent No. 5,494,495; and U.S. Patent Application Serial No. 08/348,543, "Method of Forming Button-Type Batteries and a Button-Type Battery Insulating and Sealing Gasket," listing Mark E. Tuttle as inventor, now U.S. Patent No. 5,662,718. These patent applications and resulting patents are hereby incorporated by reference. In an alternative embodiment, the battery 18 comprises a series connected pair of button type cells. Instead of using a battery, any suitable power source can be employed.

(iv) Various U.S. patent applications, which are incorporated herein by reference, disclose features that are employed in various alternative embodiments of the invention: 08/092,147, filed July 15, 1993, "Wake Up Device for a Communications System", now abandoned, and continuation application 08/424,827, filed April 19, 1995, "Wake Up Device for a Communications System", now U.S. Patent No. 5,790,946; 08/281,384, filed July 27, 1994, "Communication System Having Transmitter Frequency Control", now U.S. Patent No. 5,568,512; 07/990,918, filed December 15, 1992, now U.S. Patent No. 5,365,551, "Data Communication Transceiver Using Identification Protocol"; 07/899,777, filed June 17, 1992, "Radio Frequency Identification Device (RFID) and Method of Manufacture, Including an Electrical Operating System and Method," now abandoned; 07/921,037, filed July 24, 1992, "Anti-Theft Method for Detecting The Unauthorized Opening of Containers and Baggage," now abandoned; 07/928,899, filed August 12, 1992, "Electrically Powered Postage Stamp or Mailing or Shipping Label Operative with Radio Frequency (RF) Communications," now abandoned; and 08/032,384, filed on March 17, 1993, "Modulated Spread Spectrum in RF Identification Systems Method," [now allowed] now U.S. Patent No. 5,539,775.

(v) Preferably, the above technique for mounting integrated circuit 16 to card 20 (of Fig. 4) consists of a flip-chip mounting technique. One example of a flip-chip mounting technique is disclosed in pending U.S. Patent Application Serial No. 08/166,747, "Process of Manufacturing an Electrical



Bonding Interconnect Having a Metal Bond Pad Portion and Having a Conductive Epoxy Portion Comprising an Oxide Reducing Agent," listing Rick Lake and Mark E. Tuttle as inventors, now U.S. Patent No. 5,480,834 and incorporated herein by reference.

(vi) The multiplier cell originally developed by Gilbert employed bipolar junction transistors. It is also known to employ MOS transistors to produce a Gilbert multiplier cell. See, for example, *Analog Integrated Circuits for Communication, Principles, Simulation and Design*, Donald O. Pederson and Kartikeya Mayaram, [Kluwer] Kluwer Academic Publishers, Third Printing, 1994, pp. 431-433.